

ELECTRIC LIGHT-DUTY CRANES

CE6K



MAX. CAPACITY 2,000 LBS

6,000 FT-LBS

MAX. REACH 5 FT | 7 FT

MIN. GVWR NO MIN.

CONTROLS **ELECTRIC**

FEATURES

■ MANUAL EXTENSION

The standard boom length for the CE6K is 5 ft with an optional 7 ft.

■ POWERFUL 12V DC WINCH

Features a 900W, 12V Permanent Magnet motor, 3-stage planetary 216:1 with mechanical cone brake and permanent motor dynamic brakes together with aluminum die cast housings with cast iron drum and galvanized aircraft wire rope A7 x 19.

■ COMPACT FOOTPRINT

The CE6K includes a 10" x 10" base plate that utilizes very little cargo space mounted in multiple locations.

A LIGHT-DUTY, WORKHORSE MAST CRANE.

The CE6K is a 2,000 lb light-duty, mast service crane with your choice of boom lengths and mast sizes to meet a variety of lifting needs. This crane features an electric 12V DC winch, manual rotation, manual extension and manual elevation. The CE6K includes a standard 3-5 ft manual boom extension and an optional 4-7 ft extension.

SPECIFICATIONS

Lifting Capacities:	2,000 lbs
Crane Rating:	6,000 ft-lbs
Mounting Space:	10" x 10"
Stowed Height:	61-1/8"
Rope Diameter:	3/16" @ 60'
Line pull speed:	24.3 ft/min (Single-line)
Max. Single-line:	1,000 lbs
Max. Double-line:	2,000 lbs
Rotation:	Manual with Band Brake
Power Supply:	Electric 12V DC
Requirements:	12v DC Battery
Hydraulic Req:	No Hydraulics
Boom Elevation:	3-position (20°, 40°, 60°)
Controls:	12V DC On/Off Winch
Boom Extension 1:	Manual: 3' - 5'
Boom Extension 2:	(Optional) Manual: 4' - 7'
Minimum Vehicle Class:	No Minimum

OPTIONS & ACCESSORIES

Optional Mast Cut-Down

The CE6K includes multiple options for cutting down the mast to fit different utility bodies.

Jacklegs

Single jackleg for utility body (0 - 24") or for platform bodies (27' - 45")

Circuit Breaker Kit

Venturo Electric 12V DC cranes recommend a 150 AMP Circuit Breaker Kit to be installed as close to the vehicle battery as possible.

MAXIMUM LOAD CAPACITY CHART

CE6K - 3-5 FT AND 4-7 FT BOOM MAXIMUM CAPACITY CHART





