

27000 SERIES

PARTS & INSTALLATION MANUAL **27000 SERIES**

<u>Included in this manual:</u>

27634-PHX, 27789-PHX, 27695-PHX

- Stabilizer with Hydraulic Pullout and Hydraulic Legs
- Available in "Less Crosstube" (-LC) configuration

VENCO VENTURO INDUSTRIES LLC 12110 BEST PLACE | CINCINNATI, OHIO 45241

VENCO VENTURO O INDUSTRIES LLC D

27000 SERIES INST-28200 - 3/14/2024 (Rev: A0)

7607200A 25480 25447-1 25485 28201 28202 28203 28204 28205 28206 28207 28208	SECTION 200: INSTALLATION INSTALLATION GUIDELINES SELECTOR VALVE OVERVIEW DEPARTURE ANGLE, REAR-MOUNTED STABILIZERS LEG MOUNTING RECOMMENDED MOUNTING - 27634 & 27789 ISOMETRIC VIEW - 27634 OVERALL DIMENSIONS - 27634 LONG LEG OVERALL DIMENSIONS - 27634 SHORT LEG HYDRAULIC MAPPING - 27634 LESS-CROSSTUBE ASSY - 27634 ISOMETRIC VIEW - 27789
28212 28222 28223 28224 28225 28226 28227	HYDRAULIC MAPPING - 27634 & 27789 ISOMETRIC VIEW - 27695 RECOMMENDED MOUNTING - 27695 OVERALL DIMENSIONS - 27695 LONG LEG OVERALL DIMENSIONS - 27695 SHORT LEG HYDRAULIC MAPPING - 27695 HYDRAULIC MAPPING - 27695

SECTION 200

INSTALLATION



STABILIZER INSTALLATION GUIDELINES

Read instructions completely prior to starting installation. If this unit is to be installed on a Venturo crane body, continue to the stabilizer assembly section of this manual.

Prior to mounting the stabilizer crosstube, orient the stabilizer so the longer pullout is on the crane side of the truck.

REAR MOUNTED

Crosstube should be centered at the rear of the truck and tied into the truck frame, body longsills, and crane support. Installer is responsible for proper mounting brackets and hardware that will be needed during this process. If unit is to be mounted on a service body, do not attach crosstube to body sheet metal unless otherwise specified. Allow clearance between crosstube and body for the stabilizer legs to be fully retracted. Consult chassis up-fitter guide prior to installation for proper welding and bolting procedures to chassis.

See the 'RECOMMENDED MOUNTING TO TRUCK FRAME' page

Leg installation (refer to assembly section of manual) legs are adjustable to maintain proper ground penetration of 4" to 6". The stabilizer is designed to level the truck and not lift the chassis off of the ground. They are designed to work in conjunction with the chassis suspension to stabilize the unit with the bulk of the load being supported by the chassis suspension and tires. Tires must be set at the proper pressure according to the chassis manufacture, stabilizers fully extended, and legs deployed on firm, level ground prior to crane use.

IMPORTANT - When legs are fully retracted in the stowed position, a 15° degree departure angle between the bottom of the rear tire and the lowest point of the stabilizer is recommended.

See the 'DEPARTURE ANGLE' page

For hydraulic stabilizers, the control valve and selector valve are supplied in kit. It is the installer's responsibility to supply necessary hoses and fittings between these valves and stabilizer. Refer to proper hydraulic schematic for your particular stabilizer model.


IMPORTANT - The selector valve is designed to separate the crane and stabilizer hydraulic circuits. This will not allow stabilizer use while in crane mode.

FRONT MOUNTED

Front mounted crosstube will be located on top of the chassis frame and welded to body longsills. Additional shear plates (installer supplied) to be welded to crosstube and bolted to chassis frame. Crosstube to be spaced away from body for leg clearance when fully retracted. See assembly section of manual for pullout and leg installation detail.



INSTALLATION GUIDELINES	12-08-23A	C200
STABILIZERS	SUPERSEDES 01-17-17	25480



RECOMMENDED DEPARTURE ANGLE



** VENCO VENTURO INDUSTRIES LLC	RECOMMENDED DEPARTURE ANGLE
CINCINNATI, OHIO	
	REAR MOUNTED OUTRIGGERS

		•
DATE	PAGE	١
08-25-22A	-	
SUPERSEDES	05405	
01-18-17	25485	,
	08-25-22A SUPERSEDES	08-25-22A - SUPERSEDES 25/195

MOUNTING THE OUTRIGGER LEGS, 27000 SERIES OUTRIGGERS

FOLLOW INSTRUCTIONS FOR MOUNTING 27000 SERIES OUTRIGGER LEGS.

 DETERMINE PLACEMENT OF OUTRIGGER LEGS. REFER TO MODEL SPECIFIC 'OVERALL DIMENSIONS' PAGE.

2. USE HARDWARE & FASTENERS PROVIDED:


[8] HEX HEAD CAP SCREW;


5/8-11 X 1-1/2", GR. 8, ZINC

[8] LOCK NUT;

5/8-11, GR. 8, ZINC, NYLON-INSERT

- 3. INSERT BOLTS POINTING AWAY FROM OUTRIGGER.
- TORQUE OUTRIGGER LEG BOLTS & NUTS
 TO 190 FT-LBS EACH.
- 5. PLACE 24964 DANGER DECALS, [1] ON EACH LEG






DECAL PLACEMENT




MOUNTING THE LEGS	02-23-17	PAGE 04
27000 SERIES OUTRIGGERS	SUPERSEDES	28201




ENTURO ®	VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO
-----------------	--


RECOMMENDED MOUNTING TO TRUCK FRAME	DATE 02-23-17	PAGE 05
27634 & 27789 OUTRIGGERS	SUPERSEDES -	28202





ISOMETRIC VIEW	02-23-17	06
27634 OUTRIGGER (WITH LONG LEGS)	SUPERSEDES	28203







6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS



;	OVERALL DIMENSIONS	02-23-17	07
	27634 OUTRIGGER WITH LONG LEGS	SUPERSEDES	28204

VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO






6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS




OVERALL DIMENSIONS	02-23-17	08
27634 OUTRIGGER WITH SHORT LEGS	SUPERSEDES -	28205





HYDRAULIC MAPPING, OUTRIGGER SIDE	02-23-17	09
27634 OUTRIGGER	SUPERSEDES -	28206

ASSEMBLY OF 27634 OUTRIGGER WITH LESS-CROSSTUBE CONFIGURATION



INSERT 4' & 6' PULLOUT ASSEMBLIES INTO CROSSTUBE SEE STEP 2 BEFORE SLIDING TOGETHER



FASTEN BEARING PADS, SPACERS, & RETAINERS PAGE 17 - ITEMS 2, 3, 4, 10, 11



FASTEN BULKHEAD FITTINGS, POINTING CURB-SIDE PAGE 17 - ITEM 9



SEE HYDRAULIC MAPPING SECTION OF MANUAL REFER TO 'LETTER' TAGS ATTACHED TO PULLOUT HOSES




FASTEN END CAP COVERS FLUSH AGAINST CROSSTUBES PAGE 17 - ITEMS 5, 12, 13



PLUG WELD SHIMS PROVIDED TO REDUCE VERTICAL GAP PAGE 17 - ITEM 6 OR 7




NDUSTRIES LLC	LESS-CROSSTUBE ASSY	02-23-17	10
ΓI, OHIO	27634 OUTRIGGER	SUPERSEDES	28207






ISOMETRIC VIEW	02-23-17	11
27789 OUTRIGGER (WITH LONG LEGS)	SUPERSEDES	28208

® VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO







6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS



С	OVERALL DIMENSIONS	02-23-17	12
	27789 OUTRIGGER WITH LONG LEGS	SUPERSEDES -	28209






6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS



С	OVERALL DIMENSIONS	02-23-17	13
	27789 OUTRIGGER WITH SHORT LEGS	SUPERSEDES	28210






CINCINNATI, OHIO

HYDRAULIC MAPPING, OUTRIGGER SIDE

14 02-23-17 SUPERSEDES

27789 OUTRIGGER


28211





HYDRAULIC MAPPING, COMPARTMENT SIDE	02-23-17	15
27634 & 27789 PHX OUTRIGGERS	SUPERSEDES	28212


VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO






ISOMETRIC VIEW	02-23-17	25
27695 OUTRIGGER (WITH LONG LEGS)	SUPERSEDES -	28222


® VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO



VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO

RECOMMENDED MOUNTING TO TRUCK FRAME	02-23-17	^{PAGE} 26
27695 OUTRIGGER	SUPERSEDES -	28223







6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS



OVERALL DIMENSIONS	02-23-17	27
27695 OUTRIGGER WITH LONG LEGS	SUPERSEDES -	28224






6" RANGE ADJUSTABLE FOR LEG MOUNTING AT 2" INCREMENTS



CINCINNATI, OHIO

.C	OVERALL DIMENSIONS	02-23-17	PAGE 28
	27695 OUTRIGGER WITH SHORT LEGS	SUPERSEDES -	28225






HYDRAULIC MAPPING, OUTRIGGER SIDE

27695 OUTRIGGER

29

28226






HYDRAULIC MAPPING, COMPARTMENT SIDE	02-23-17	30
27695 OUTRIGGER	SUPERSEDES	28227


SECTION 400


REPLACEMENT PARTS


















PARTS BREAKDOWN, SECTIONS	02-23-17	16
27634 & 27789 OUTRIGGERS	SUPERSEDES -	28213


PARTS BREAKDOWN, CROSSTUBE ASSEMBLY, 27634 & 27789 OUTRIGGERS

27634 & 27789 OUTRIGGERS CROSSTUBE ASSEMBLY					
#	DESCRIPTION	QTY	PART #		
1	CROSSTUBE; DUAL-TUBE, 27000 SERIES	1	27631 / 27788		
2	BEARING PAD; 3 1/8" X 3 1/2" X 3/8", UHMW	2	27718		
3	BEARING SPACER; 3 1/8" X 2" X 1/2", CROSSTUBE	2	27719		
4	PLATE; BEARING RETAINER, 27000 SERIES O.R.'S	2	27643		
5	COVER; END CAP, DUAL CROSSTUBE, 27000 SERIES	2	27644		
6	SHIM; VERTICAL GAP, 10 GA, 27000 SERIES O.R.'S	0-2	27631J		
7	SHIM; VERTICAL GAP, 14 GA, 27000 SERIES O.R.'S	0-2	27631K		
8	HOSE ASS'Y; 73" LONG, O.R. TO COMPARTMENT	4	27680		
9	FITTING; BULKHEAD, ELBOW, 90°, 6MJ-6MJ	8	H2701LN-0606		
10	HEX HEAD CAP SCREW; 3/8-16 X 3/4", GR. 5, ZINC	8	!HHCS03816075-5		
11	LOCK WASHER; 3/8", GR. 5, ZINC	8	LWSH-038		
12	HEX HEAD CAP SCREW; 1/4-20 X 1/2", STAINLESS	8	!HHCS02520050S		
13	LOCK WASHER; 1/4", STAINLESS	8	!LWSH-025S		

REFERENCE PAGE 18



	DATE	PAGE
PARTS BREAKDOWN	02-23-17	17
	SUPERSEDES	00044
CROSSTUBE ASSEMBLY	-	28214





VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO


PARTS BREAKDOWN, CROSSTUBE ASSEMBLY	02-23-17	18
27634 & 27789 OUTRIGGERS	SUPERSEDES -	28215

	27634 & 27789 OUTRIGGERS 6' PULLOUT ASSEMBLY					
#	DESCRIPTION	QTY	PART #			
1	PULLOUT TUBE; 6' SIDE, 27000 SERIES O.R.'S	1	27632			
2	EXTENSION CYLINDER; 72" STROKE, 2" BORE	1	27635			
3	BEARING PAD; 3 1/8" X 3 1/2" X 3/8", UHMW	1	27718			
4	SHAFT; INBOARD, EXT. CYL., CROSSTUBE	1	27638			
5	SHAFT; OUTBOARD, EXT. CYL., PULLOUT	1	27639			
6	SET COLLAR; 3/4" I.D., 1 1/4" O.D.	4	00210			
7	BUSHING; 14 GA, 3/4" I.D., 1 1/4" O.D., ZINC	2	12534-14			
8	BUSHING; 10 GA, 3/4" I.D., 1 1/4" O.D., ZINC	4	12534-1			
9	CLAMP SUPPORT; HOSE CLAMP, CYL. MOUNT	1	27689			
10	HOSE CLAMP, ADJUSTABLE, GROMMET	2	27700			
11	HOSE ASS'Y; CROSSOVER, UP & DOWN	2	27679			
12	HOSE ASS'Y; RETRACTION, CYLINDER	1	27677			
13	HOSE ASS'Y; EXTENSION, CYLINDER	1	27675			
14	FITTING; ADAPTER, ELBOW, 90°, 6MJ-6MO	2	H6801L-0606			
15	FITTING; BULKHEAD, ELBOW, 90°, 6MJ-6MJ	2	H2701LN-0606			

REFERENCE PAGE 20



PARTS BREAKDOWN	02-23-17	19
6' PULLOUT ASSEMBLY	SUPERSEDES -	28216



ENTURO®

VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO


PARTS BREAKDOWN, 6' PULLOUT ASSEMBLY	02-23-17	20
27634 & 27789 OUTRIGGERS	SUPERSEDES -	28217

PARTS BREAKDOWN, 4' PULLOUT ASSEMBLY, 27634 OUTRIGGERS

	27634 OUTRIGGERS 4' PULLOUT ASSEMBLY					
#	DESCRIPTION	QTY	PART #			
1	PULLOUT TUBE; 4' SIDE, 27000 SERIES O.R.'S	1	27633			
2	EXTENSION CYLINDER; 48" STROKE, 2" BORE	1	25082			
3	BEARING PAD; 3 1/8" X 3 1/2" X 3/8", UHMW	1	27718			
4	SHAFT; INBOARD, EXT. CYL., CROSSTUBE	1	27638			
5	SHAFT; OUTBOARD, EXT. CYL., PULLOUT	1	27639			
6	SET COLLAR; 3/4" I.D., 1 1/4" O.D.	4	00210			
7	BUSHING; 14 GA, 3/4" I.D., 1 1/4" O.D., ZINC	2	12534-14			
8	BUSHING; 10 GA, 3/4" I.D., 1 1/4" O.D., ZINC	4	12534-1			
9	CLAMP SUPPORT; HOSE CLAMP, CYL. MOUNT	1	27689			
10	HOSE CLAMP, ADJUSTABLE, GROMMET	2	27700			
11	HOSE ASS'Y; CROSSOVER, UP & DOWN	2	27678			
12	HOSE ASS'Y; RETRACTION, CYLINDER	1	27676			
13	HOSE ASS'Y; EXTENSION, CYLINDER	1	27675			
14	FITTING; ADAPTER, ELBOW, 90°, 6MJ-6MO	2	H6801L-0606			
15	FITTING; BULKHEAD, ELBOW, 90°, 6MJ-6MJ	2	H2701LN-0606			



PARTS BREAKDOWN	02-23-17	PAGE 21
4' PULLOUT ASSEMBLY	SUPERSEDES	28218



ENTURO[®]


VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO


PARTS BREAKDOWN, 4' PULLOUT ASSEMBLY	02-23-17	22
27634 OUTRIGGERS	SUPERSEDES -	28219

PARTS BREAKDOWN, HYDRAULIC LEGS, 27634 & 27789 OUTRIGGERS

	27634 & 27789 OUTRIGGERS HYDRAULIC LEG ASSEMBLIES	LONG LEGS	SHORT LEGS	QTY EACH PER LEG
#	DESCRIPTION	Ġ	ΤΥ	PART#
1	LEG; HYDRAULIC, LONG, 30" STROKE (LEFT)	1	ı	27637-LL
2	LEG; HYDRAULIC, SHORT, 20" STROKE (LEFT)	-	1	27637
3	COVER; LONG LEG, LEFT SIDE	1	-	25068-1
4	COVER; SHORT LEG, LEFT SIDE	•	1	25069-1
5	SPACER; COVER, MOUNTING, HYD. LEGS	3	3	25070
6	VALVE BLOCK; P.O. CHECK CARTRIDGE	1	1	22765-LF
7	HOSE ASS'Y; LEG RETURN, LONG LEG	1	-	25061
8	HOSE ASS'Y; LEG RETURN, SHORT LEG	-	1	27672
9	HOSE ASS'Y; LEG UP & DOWN, LONG LEG	2	-	25152
10	HOSE ASS'Y; LEG UP & DOWN, SHORT LEG	-	2	27673
11	FITTING; ELBOW, 90°, LONG, 6MJ-6MO	1	1	H6801L-0606
12	FITTING; COUPLING, STRAIGHT, 6FJX-6FJX	1	1	H6565-0606
13	FITTING; ADAPTER, STRAIGHT, 6MJ-8MP	1	1	H2404-0608
14	FITTING; ADAPTER, ELBOW, 90°, 4MJ-6MO	1	1	H6801-0406
15	FITTING; ADAPTER, T-SHAPE, 4FJX-4MJ-4MJ	1	1	H6602-040404
16	FITTING; ADAPTER, ELBOW, 90°, 4MJ-4FX	1	1	H6500-0404
17	FITTING; ADAPTER, STRAIGHT, 4MJ-6MO	1	1	H6400-0406
18	FITTING; ELBOW, 90° EXTRA LONG, 4MJ-4MO	1	1	H6801LL-0404
19	FLAT WASHER; 5/16", STAINLESS	3	3	!FWSH-031S
20	LOCK NUT; 5/16-18, NY LON INSERT, STAINLESS	3	3	!LNUT-031NS
21	HEX HEAD CAP SCREW; 5/8-11 X 1 1/2", GR. 8	4	4	!HHCS06311150-8
22	LOCK NUT; 5/8-11, NYLON INSERT, GR.8, ZINC	4	4	!LNUT-06311-8










PARTS BREAKDOWN, SECTIONS	02-23-17	31
27695 OUTRIGGER	SUPERSEDES	28228

PARTS BREAKDOWN, CROSSTUBE ASSEMBLY, 27695 OUTRIGGERS

	27695 OUTRIGGERS CROSSTUBE ASSEMBLY					
#	DESCRIPTION	QTY	PART #			
1	CROSSTUBE; 0' X 5', SINGLE TUBE	1	27693			
2	BEARING PAD; 3 1/8" X 3 1/2" X 3/8", UHMW	1	27718			
3	BEARING SPACER; 3 1/8" X 2" X 1/2", A36 HRS	1	27719			
4	PLATE; BEARING RETAINER, 27000 SERIES O.R.'S	1	27643			
5	SHIM; VERTICAL GAP, 10 GA, 27000 SERIES O.R.'S	0-1	27631J			
6	SHIM; VERTICAL GAP, 14 GA, 27000 SERIES O.R.'S	0-1	27631K			
7	FITTING; BULKHEAD, ELBOW, 90°, 6MJ-6MJ	4	H2701LN-0606			
8	HEX HEAD CAP SCREW; 3/8-16 X 3/4", GR. 5, ZINC	4	!HHCS03816075-5			
9	LOCK WASHER; 3/8", GR. 5, ZINC	4	!LWSH-038			



PARTS BREAKDOWN	02-23-17	PAGE 32
CROSSTUBE ASSEMBLY	SUPERSEDES -	28229



ENTURO®


VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO

PARTS BREAKDOWN, CROSSTUBE ASSEMBLY	02-23-17	33
27695 OUTRIGGER	SUPERSEDES -	28230

PARTS BREAKDOWN, 5' PULLOUT ASSEMBLY, 27695 OUTRIGGER

	27695 OUTRIGGER 5' PULLOUT ASSEMBLY				
ITEM	DECRIPTION	QTY	PART#		
1	PULLOUT TUBE; 5' EXT., 27000 SERIES O/R	1	27694		
2	EXTENSION CYLINDER; 60" STROKE, 2" BORE	1	27692		
3	BEARING PAD; 3 1/8" x 3 1/2" x 3/8", UHMW	1	27718		
4	SHAFT; INBOARD, EXT. CYL., CROSSTUBE	1	27638		
5	SHAFT; OUTBOARD, EXT. CYL., PULLOUT	1	27639		
6	SET COLLAR; 3/4" ID, 1 1/4" OD	4	'00210		
7	BUSHING; 14GA, 3/4" ID, 1 1/4" OD, ZINC	2	12534-14		
8	BUSHING; 10GA, 3/4" ID, 1 1/4" OD, ZINC	4	12534-1		
9	CLAMP SUPPORT; HOSE CLAMP, CYL. MOUNT	1	27689		
10	HOSE CLAMP; ADJUSTABLE, GROMMET	2	27700		
▲ 11	HOSE ASS'Y; CROSSOVER, LEG UP/DOWN	2	27715		
12	HOSE ASS'Y; RETRACTION, CYLINDER	1	27714		
13	HOSE ASS'Y; EXTENSION, CYLINDER	1	27713		
14	FITTING; ADAPTER, ELBOW, 90°, 6MJ-6MO	2	H6801L-0606		
15	FITTING; BULKHEAD, ELBOW, 90°, 6MJ-6MJ	2	H2701LN-0606		







VENCO VENTURO INDUSTRIES LLC CINCINNATI, OHIO


PARTS BREAKDOWN, 5' PULLOUT ASSEMBLY	02-23-17	35
27695 OUTRIGGER	SUPERSEDES -	28232

PARTS BREAKDOWN, LONG LEGS ASSEMBLY, 27695 OUTRIGGER

	27695 OUTRIGGER LONG LEGS ASSEMBLY	RIGHT LEG	LEFT LEG	QTY EACH PER LEG
#	DESCRIPTION	Q.	TY	PART #
1	LEG; HYDRAULIC, LONG, 30" STROKE, RIGHT	1	-	25055-1
2	LEG; HY DRAULIC, LONG, 30" STROKE, LEFT	-	1	25055-2
3	COVER; LONG LEG, LEFT SIDE	-	1	25068-1
4	COVER; LONG LEG, RIGHT SIDE	1	-	25068-2
5	SPACER; COVER, MOUNTING, HYD. LEGS	3	3	25070
6	VALVE BLOCK; P.O. CHECK CARTRIDGE	1	1	22765-LF
7	HOSE ASS'Y; LEG RETURN, LONG LEG	1	1	25061
8	HOSE ASS'Y; LEG UP & DOWN, LONG LEG	2	2	25152
9	FITTING; ELBOW, 90°, LONG, 6MJ-6MO	1	1	H6801L-0606
10	FITTING; COUPLING, STRAIGHT, 6FJX-6FJX	1	1	H6565-0606
11	FITTING; ADAPTER, STRAIGHT, 6MJ-8MP	1	1	H2404-0608
12	FITTING; ADAPTER, ELBOW, 90°, 4MJ-6MO	1	1	H6801-0406
13	FITTING; ADAPTER, T-SHAPE, 4FJX-4MJ-4MJ	1	1	H6602-040404
14	FITTING; ADAPTER, ELBOW, 90°, 4MJ-4FX	1	1	H6500-0404
15	FITTING; ADAPTER, STRAIGHT, 4MJ-6MO	1	1	H6400-0406
16	FITTING; ELBOW, 90° EXTRA LONG, 4MJ-4MO	1	1	H6801LL-0404
17	FLAT WASHER; 5/16", STAINLESS	3	3	!FWSH-031S
18	LOCK NUT; 5/16-18, NYLON INSERT, STAINLESS	3	3	!LNUT-031NS
19	HEX HEAD CAP SCREW; 5/8-11 X 1 1/2", GR. 8	4	4	!HHCS06311150-8
20	LOCK NUT; 5/8-11, NYLON INSERT, GR.8, ZINC	4	4	!LNUT-06311-8



PARTS BREAKDOWN	02-23-17	36
LONG LEGS ASSEMBLY	SUPERSEDES -	28233






PARTS BREAKDOWN, SHORT LEGS ASSEMBLY, 27695 OUTRIGGER

27695 OUTRIGGER SHORT LEGS ASSEMBLY		RIGHT LEG	LEFT LEG	QTY EACH PER LEG	
#	DESCRIPTION	Q.	TY	PART #	
1	LEG; HYDRAULIC, SHORT, 20" STROKE, RIGHT	1	-	25083-2	
2	LEG; HYDRAULIC, SHORT, 20" STROKE, LEFT	-	1	25083-1	
3	COVER; SHORT LEG, LEFT SIDE	-	1	25064-1	
4	COVER; SHORT LEG, RIGHT SIDE	1	-	25064-2	
5	SPACER; COVER, MOUNTING, HYD. LEGS	3 3		25070	
6	VALVE BLOCK; P.O. CHECK CARTRIDGE	1	1	22765-LF	
7	HOSE ASS'Y; LEG RETURN, SHORT LEG	1	1	27672	۱
8	HOSE ASS'Y; LEG UP & DOWN, SHORT LEG	2	2	27673	۱
9	FITTING; ELBOW, 90°, LONG, 6MJ-6MO	1	1	H6801L-0606	
10	FITTING; COUPLING, STRAIGHT, 6FJX-6FJX	1	1	H6565-0606	
11	FITTING; ADAPTER, STRAIGHT, 6MJ-8MP	1	1	H2404-0608	
12	FITTING; ADAPTER, ELBOW, 90°, 4MJ-6MO	1	1	H6801-0406	
13	FITTING; ADAPTER, T-SHAPE, 4FJX-4MJ-4MJ	1	1	H6602-040404	
14			1	H6500-0404	
15			1	H6400-0406	
16	FITTING; ELBOW, 90° EXTRA LONG, 4MJ-4MO	1	1	H6801LL-0404	
17	FLAT WASHER; 5/16", STAINLESS	3	3	!FWSH-031S	
18	LOCK NUT; 5/16-18, NYLON INSERT, STAINLESS	LON INSERT, STAINLESS 3 :		!LNUT-031NS	
19	HEX HEAD CAP SCREW; 5/8-11 X 1 1/2", GR. 8	4	4	!HHCS06311150-8	
20	LOCK NUT; 5/8-11, NYLON INSERT, GR.8, ZINC	4	4	!LNUT-06311-8	

	VENCO VENTURO INDUSTRIES LLC	DADTO DDE 41/D 014/41	07-12-19A	PAGE 38
ENTUR	CINCINNATI, OHIO		SUPERSEDES	20225
		SHORT LEGS ASSEMBLY	02-23-17	28235



® VENCO VENTURO INDUSTR	PARTS BREAKDOWN	02-23-17	39
CINCINNATI, OHIO	SHORT LEGS ASSEMBLY	SUPERSEDES -	28236

VENTURO CRANES LIMITED WARRANTY POLICY



Venturo products are built to last...we guarantee them.

As a purchaser of any new Venturo product covered by warranty, you will receive 1 year of the most complete coverage available...and, at no added cost to you.

1-Year Limited Warranty Policy

This limited policy warrants new products of Venturo to be free from defects in material and workmanship for a period of one (1) year from date of original installation. OEM products or accessories purchased by Venturo as part of or offered with our product will carry the OEM manufacturer's respective warranty. Our warranty covers:

- Repair or replacement of product
- Labor to repair or replace product
- Freight to return and/or replace product

We shall not be liable for any contingent liabilities arising out of the improper function of any products. Warranty shall become void if the product is improperly installed, modified, damaged, abused or used for application other than intended use. There is no warranty of merchantability, fitness for a particular purpose, warranty arising from course of dealing or usage of trade, or any other implied or expressed warranty, except as made specifically herein. This warranty supersedes all previous warranties, written or implied.

Warranty Claims

Venco Venturo Industries LLC will make a good faith effort for prompt correction or other adjustment with respect to any product, which proves to be defective after our inspection and within the warranty period. Before any repairs are attempted or before returning any product, your Venturo Distributor is required to obtain a warranty claim number. This number is necessary for any claim to be considered. To obtain a warranty claim number, Venturo requires the model and serial number. Only authorized Venturo Distributors can perform warranty. For the name and address of your local Venturo Distributor call the **Warranty Claim Department - 513-772-8448.**

WARNING - It is the responsibility of the installer to ensure the installation is completed according to the manufacturer's recommendations, ensure the ultimate user understands how to operate product in a safe manner, and understands the need for regular service and maintenance by an authorized Venturo Distributor. No modifications or alterations may be made to any Venturo product without the expressed written consent of Venco Venturo Industries LLC. Installation of any Venturo product must be done by an authorized Venturo Distributor, to the standards of the industry; including maintenance, service and affixing of all instruction, safety and warning decals. Users should be instructed as to the safe operation at time of delivery. Maintenance, service, operation and safety warning decals are available on request from Venco Venturo Industries LLC.

VENCO VENTURO INDUSTRIES LLC

12110 BEST PLACE | CINCINNATI, OHIO 45241 P: 800-226-2238 | F: 513-326-5427 www.venturo.com

Revised: January 2015 12-00073_VNT1-D